

#### INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:

C07C 43/178, C08G 65/28

(11) International Publication Number:

WO 91/13849

A1

(43) International Publication Date:

19 September 1991 (19.09.91)

(21) International Application Number:

PCT/AU90/00565

(22) International Filing Date:

23 November 1990 (23.11.90)

(30) Priority data:

PJ 9055

9 March 1990 (09.03.90)

ΑU

(71) Applicant (for all designated States except US): ICI AUS-TRALIA OPERATIONS PROPRIETARY LIMITED [AU/AU]; 1 Nicholson Street, Melbourne, VIC 3000

(72) Inventor; and

- (75) Inventor/Applicant (for US only): COOK, Iain [GB/AU] Unit 2, 8 Murray Street, West Brunswick, VIC 3055
- (74) Agent: DAVY, John, R.; Industrial Property Section, ICI Australia Operations Proprietary Limited, 1 Nicholson Street, P.O. Box 4311, Melbourne, VIC 3001 (AU).

(81) Designated States: AT (European patent), AU, BE (European patent), CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent), US.

**Published** 

With international search report.

(54) Title: FATTY ALCOHOL ALKOXYLATE

**(I)** 

#### (57) Abstract

A compound of formula (I) where R, which may be the same or different, is selected from at least one of hydrogen, methyl, ethyl and phenyl, at least one R on each -OCHR-CHR- unit being hydrogen; where m is an integer selected from 1-100; where n is an integer selected from 8 and 9. The preferred process of preparation is by the reaction of alkylene oxide with linoleyl alcohol in the presence of a catalyst which is a Bronsted base. The compounds are useful as reactive surfactants in aqueous emulsion polymerisation processes.

#### FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinca	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	iT	Italy	RO	Romania
CF	Central African Republic	JР	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic	SE	Sweden
CH	Switzerland		of Korea	SN	Senegal
Ci	Côte d'Ivoire	· KR	Republic of Korea	SU	Soviet Union
CM	0	11	Liechtcostein	TD	Chad
-		LK	Sri Lanka	TG	Togo
cs	Czechoslovakia	LU	Luxembourg	us	United States of America
DE	Germany	MC	Monaco	-	
DK	Denmark	, MC	Monaço		

MARCHAN SANT

#### FATTY ALCOHOL ALKOXYLATE

This invention relates to alkoxylates of unsaturated fatty alcohols and to their use in surface coating compositions.

It has been known for some time that it is possible to prepare molecules which consist of a hydrocarbon chain and an oxyalkylene chain (usually an oxyethylene chain), and such compounds have been useful, for example, as surfactants in a variety of end uses, one typical example being surface coatings. The hydrocarbon chain may be derived from a long chain fatty alcohol, a very common example being oleyl alcohol. This alcohol has a single double bond but this double bond is very unreactive under normal polymerisation conditions and oleyl ethoxylates have enjoyed wide use in many fields where the presence of this unsaturation is of no consequence.

In those cases where, in that part of the hydrocarbon alkoxylate which is lipophilic, there is desired the presence of unsaturation which is relatively reactive with respect to an addition 5 polymerisation reaction, special compounds have been devised. Thus, while compounds such as oleyl ethoxylate will work in the multi-polymer particle dispersions disclosed in United States Patent 4.413.073, the preferred unsaturated surfactants 10 described in this disclosure are more reactive and the most preferred surfactants have multiple double bonds derived from such molecules as pentaerythritol triallyl ether. Similarly, in European Published Application 0 002 252, the applicants use allylic 15 bonds for reaction with the fatty acid chains of the water-borne alkyd resin which is described in that document.

It has now been found that it is possible to provide an unsaturated fatty alcohol alkoxylate

whose unsaturation is usefully reactive. There is therefore provided, according to the present invention, a compound of the formula I

$$\mathsf{CH_3^-(CH_2)_{13-n}^-CH=CH-CH=CH-(CH_2)_{n}^-OCH-CH-(OCH-CH)_{m}^-OH}$$

I

where R, which may be the same or different, is selected from at least one of hydrogen, methyl, ethyl and phenyl, at least one R on each -OCHR-CHR-unit being hydrogen; where m is an integer selected from 1-100; where n is an integer selected from 8 and 9.

The oxyalkylene chain of the compound is of 2-101 and preferably 6-50 units in length. The nature of the individual units is very much determined by the end use to which the compound will 5 be put. For example, if the compound is to be a reactive surfactant in an aqueous emulsion system, the oxyalkylene chain will consist mainly, and preferably solely, of oxyethylene units. Provided that the desired balance between the lipophilic and 10 hydrophilic portions of the surfactant can be achieved, it is possible to include a proportion of oxypropylene, oxyethylethylene or oxyphenylethylene units. These are advantageously located on the chain adjacent to the lipophilic portion as they ·15 increase the overall lipophilicity of the molecule. The preferred oxyalkylene unit is the oxyethylene unit; those compounds according to the invention which comprise oxyalkylene units other than oxyethylene units are useful as intermediates for other products, but the oxyethylene unit is the most 20 useful and preferably all of the oxyalkylene units are oxyethylene units.

It is particularly preferred that the double bonds in the compounds of the invention exhibit opposite geometrical isomerism, that is, one is trans and the other <u>cis</u>, not both <u>cis</u> or <u>trans</u>.

Accordingly we provide in a particularly preferred embodiment of the invention a compound of formula I as hereinbefore described in which the double bonds exhibit opposite geometrical isomerism.

20

The compounds of this invention may be synthesised by any convenient means. A particularly valuable method of preparing the preferred compounds forms part of this invention. There is therefore 5 provided a method of preparing a compound according to the invention comprising the reaction of alkylene oxide with linoleyl alcohol in the presence of a base catalyst which is a Bronsted base.

It will readily be appreciated that the 10 structure of this alcohol is different to that of the non-oxyalkylene chain part of the compounds; linoleyl alcohol is cis-9, cis-12-octadecadienol. It has been found that, under the conditions of the alkoxylation, one of the double bonds positioned at 15 the 9- or the 12- position moves into a conjugated arrangement with respect to the other, and at the same time this bond changes its stereochemical configuration such that there is one cis-bond and one trans-bond.

The linoleyl alcohol for use in this aspect of the invention may be a pure substance. Alternatively, it is possible to use one of the commercially-available mixtures of fatty alcohols which contain a significant proportion of linoleyl 25 alcohol. It has been found that the alkoxylation of such mixtures can give a product which is acceptable for many uses and which is considerably cheaper than the alkoxylated pure alcohol. However, it is essential that at least 15% and preferably at least 40% by weight of the mixture be linoleyl alcohol. Examples of suitable commercially-available mixtures can be found in the "Ocenol" range of product of Henkel KGaA, one suitable one being the "110-130" grade.

The invention also, therefore, provides a chemical composition which is essentially a blend of alkoxylated fatty alcohols, at least 15% (preferably at least 40%) by weight of which are compounds of formula I — as hereinabove described.

By "Bronsted base" is meant a base which is capable of abstracting a proton. While any Bronsted base will work to some extent in the invention, it will readily be appreciated by the skilled worker 10 that, for some bases, the obtaining of acceptable yields will require unacceptably long reaction times and/or unacceptably severe reaction conditions, and the use of such bases is not therefore a practical proposition. As a general rule, reaction times should be no longer than 48 hours and reaction conditions no more severe than 160°C temperature and 1000 kPa pressure. Any Bronsted base which gives an acceptable yield under conditions such as these is especially preferred for use in this invention. 20 Examples of preferred bases are the alkali metal and alkaline earth metal alkoxides and hydroxides,

20 Examples of preferred bases are the alkali metal and alkaline earth metal alkoxides and hydroxides, particularly sodium methoxide and potassium hydroxide. Other suitable bases include metal hydrides, such as sodium hydride.

The compounds of this invention are useful in a number of applications, but compounds with appropriate HLB values are especially useful as reactive surfactants in the formulation of aqueous dispersions for use in water-borne coating compositions. They are, for example, useful in the preparation of polymer particles.

In a further embodiment of the invention we therefore provide a process for preparation of polymer particles, the process comprising polymerising in aqueous media unsaturated monomer in the presence of at least one compound of formula I as hereinbefore described.

The nature of the unsaturated monomer is not narrowly critical and particles may be prepared by this process using a wide range of monomers commonly 10 used in suspension and emulsion polymerisation, for example one or more of the monomers selected from the group of the  $C_1-C_{12}$  (preferably the  $C_1-C_4$ ) alkyl acrylates and methacrylates, (meth)allyl acrylates and methacrylates, glycidyl methacrylate and vinyl acetate, hydroxy, butyl acrylate, 2-ethoxy ethyl acrylate, glycidyl acrylate, methyl methacrylate, ethyl methacrylate, butyl methacrylate, stearyl methacrylate, methacrylic acid, methoxy propyl methacrylate, cyclohexyl methacrylate, benzyl methacrylate, hydroxyethyl methacrylate, hydroxy 20 propyl methacrylate, dimethylaminoethyl methacrylate, N-butoxymethyl methacrylamine, N-buoxymethyl acrylamide, glycidyl methacrylate, vinyl acetate, vinyl propionate, styrene, 1-methyl styrene, vinyl toluene, methoxy styrene and vinyl 25 pyridine, di-butyl maleate and vinyl chloride.

The known techniques of suspension and emulsion polymerisation, including the selection of appropriate polymerisation initiators, are applicable to the preparation of the aqueous dispersion of our invention. As is understood in the art polar monomers may need to be used in combination with less polar monomers to achieve the appropriate aqueous dispersion. Either thermally-activated or redox initiators may be used.

Due to the reactivity of the compounds of formula I they have been found to provide a particularly stable dispersion of polymer particles therefore providing a significant improvement in aqueous coating compositions. In such applications, the compounds of formula I may be used alone or in combination with other surfactants, for example anionic surfactant. We therefore further provide an aqueous dispersion of polymer particles stabilized by at least one compound of formula I according to any one of claims 1 to 5.

The aqueous dispersion may comprise additives which adapt it for use as a coating composition.

Coating compositions may be prepared by
15 blending standard additives such as pigments,
extenders, antifoams, thickeners and fungicides into
the dispersion in art-recognied quantities using
known methods.

An example of polymer particles which may be produced using the compounds of formula I is described in US Patent 4,413,073.

A further particularly preferred example of polymer particles which may be prepared using compounds of formula I are core-sheath particles of the type described in Australian Patent Application No. 52006/90. Such particles will have diameters of less than 100 nm and comprise a core of polymer of an ethylenically unsaturated monomer and a sheath comprising polyoxyalkylene chains wherein said polyoxyalkylene chains are derived from the covalent bonding of compounds of formula I with the core addition-polymer.

The invention is further described with reference to the following example in which all parts are expressed by weight.

#### Example 1

5

Preparation of compounds according to the invention, the compounds having 12 moles ethylene oxide per mole of unsaturated chain.

49.6 parts of linoleyl alcohol (cis-9-cis-12-octadien-1-ol; 99% ex Sigma) was 10 dissolved in 250 parts xylene containing 0.03 parts each of phenothiazine and 4-methoxyphenol. 1.8 parts 30% sodium methoxide in methanol was then rapidly added to the stirred solution which was then transferred to a clean dry stainless steel autoclave at 35°C under slight vacuum. A further 50 parts xylene was used to rinse the residues from the flask and the line. The reactor was twice evacuated and purged with nitrogen, then heated under vacuum to 70°C, at which point xylene began to distil over. 20 The autoclave was evacuated and purged with nitrogen once more, and was then pressurised to 70 kPa and heated to 140°C. Ethylene oxide (98 parts) was charged batchwise over 2 h, keeping the temperature below 143°C and the pressure below 400 kPa. The reaction mixture was allowed to react out at 142  $\pm$ 2°C over 1 1/2 h, cooled to 55°C, evacuated and purged and discharged into a solution of 0.84 parts of orthophosphoric acid in 5 parts water. Volatiles were removed under vacuum (rotary evaporator 30 followed by oil pump at 0.5-1 mm Hg) at  $70^{\circ}$ C. The product, a pale yellow oil was filtered through "Celite" whilst warm. The cloud point (10% w/w in water) was 77-77.5°C. Carbon-13 NMR showed that the 15

25

linolenyl alcohol double bond peaks (127.95, 128.02, 130.12, 130.20 ppm from tetramethylsilane (TMS)) had disappeared, to be replaced by peaks due to the cis-9-trans-10 and trans-10-cis-12 isomers in approximately equal proportions (125.60, 128.59/128.62, 129.93/129.99, 134.59 ppm from TMS).

#### Example 2

Preparation of compounds according to the invention from a commercially-available alcohol mixture, the compounds having 10 moles ethylene oxide per mole of unsaturated chain.

616 parts of "Ocenol" (Trade Mark) 110-130 (ex Henkel KGaA), (a commercially available mixture of fatty alcohols being approximately 40% by weight linoleyl alcohol) was warmed to dissolve any separated components. It was then charged to an autoclave and purged with nitrogen. There was then slowly added 18 parts of 30% sodium methoxide. vessel containing the sodium methoxide was rinsed 20 three times with 15 parts ethanol and this ethanol slowly charged with stirring. The autoclave was evacuated, purged with nitrogen and then evacuated and heated to 130°C, all volatile materials being stripped off. The evacuation and purging with nitrogen was repeated and 1034 parts ethylene oxide was then added over a period of 2 hours, the autoclave being maintained at  $130^{\circ}$ - $145^{\circ}$ C and 100-500kPa pressure. Reaction was continued for 30 minutes, and the contents of the autoclave were then cooled and volatiles were stripped off under vacuum. The cloud point of a 10% w/w mixture with water was

found to be 71.5°C - 72.5°C. The pH of the product was reduced to 5.5 by the addition of an 85% solution of orthophosphoric acid in distilled water (9 parts was needed). The product was finally stripped under vacuum at 115°C for 3 hours and filtered while hot through "Celite".

The final component was a pale orange-yellow solid. NMR analysis showed that the 9,12-arrangement of the double bonds of the linoleyl alcohol had changed to a mixture of 9,11- and 10,12-arrangements, to give compounds according to the invention.

#### Example 3

Preparation of compounds according to the invention, the compounds having the approximate composition 1 mole unsaturated chain to 40 moles ethylene oxide.

The compound was made in an analogous manner to example 2, with 185 parts "Ocenol" 110-130 and 1215 parts ethylene oxide. The product was an off-white solid which NMR analysis showed to consist mainly of a mixture of oleyl, 9,11- and 10,12-double bond-containing compounds.

#### Example 4

Preparation of compounds according to the invention using two alkylene oxides (in this case propylene and ethylene oxides in the approximate unsaturated chain: propylene oxide:ethylene oxide mole ratio of 1:4:10).

30 "Ocenol" 110-130 (449 parts) was charged into a clean, dry autoclave at 50°C and evacuated and purged with nitrogen. 18.0 parts 30% sodium

methoxide in methanol, followed by 3  $\times$  20 ml. rinse methanol was then charged to the autoclave with stirring. The reactor was evacuated and purged and then heated to 120°C under vacuum. Propylene oxide 5 (400 parts) was added over 2 h at 130-135 C and 100-200 kPa pressure. The reaction contents were reacted out for 1 1/2 h and the reactor was then evacuated and purged to remove any residual propylene oxide. Ethylene oxide (753 parts) was 10 then added over 1.2 h, reacted out for 1 h, cooled to 75°C, stripped under vacuum and neutralised with 10.4 parts 85% phosphoric acid in 60 ml water. The product, a pale orange-yellow liquid, was dehydrated under vacuum to 120°C for 3 h and filtered while hot through "Celite". The cloud point of a 10% w/w solution was 55.5-56.5°C. NMR analysis confirmed the alteration of the 9,12- unsaturated double bond arrangement into a mixture of 9,11- and 10,12arrangements.

#### 20 <u>Example 5</u>

The use of a compound according to the present invention in the preparation of an aqueous dispersion of addition polymer particles.

The materials and quantities used were as follows:

	Stage	A	deionised water	106.74	parts
	, ou g	••	"Fenopon" (trade mark)	3.30	
5			CO 436 surfactant		
•			30% HC1	3 dr	ps
			1% ferrous sulphate	4.18	
			solution		
		В	t-butyl perbenzoate	0.18	
10		С	methyl methacrylate	113.37	
			butyl acrylate	97.77	
			methacrylic acid	3.00	
			compound from Example 2	15.62	
		D	deionised water	143.81	
15			sodium erythorbate	10.49	
			(10% aqueous solution	1)	
		_		1 5	Λ

E t-butyl perbenzoate 1.54

The stage A materials were added to a reaction vessel (the hydrochloric acid being sufficient to reduce the pH of the mixture to about 2) and were stirred under nitrogen for about 20 minutes.

The stage C monomers were mixed in another vessel and the Example 2 compound melted and added to them. The stage D materials were then added to the stage C materials and the resultant mixture was mixed vigorously to form a coarse emulsion.

20

The tert-butyl perbenzoate of stage B was added to the stage A materials in the reaction vessel and stirring was continued for 10 minutes to emulsify it. 10% of the stage C + stage D mixture was then added and stirred in, stirring was stopped and the mixture allowed to exotherm, cooling being applied to keep the temperature below 30°C.

After 30 minutes, the stage E tert-butyl perbenzoate was added to the reaction vessel with stirring and the remainder of the stage C + stage D materials fed in over a period of 80 minutes, maintaining the temperature at 30°C. When addition was complete, stirring and cooling were continued for a further 60 minutes. After cooling to 20°C, ammonium hydroxide solution was added to raise the pH to 8.5.

The resulting product was a fine particle size (83 nm average diameter measured using a "Nanosizer") aqueous dispersion of 46.0% solids contents.

The claims defining the invention are as follows:

A compound of the formula I

$$\begin{array}{c} \text{R} \quad \text{$$

I

where R, which may be the same or different, is selected from hydrogen, methyl, ethyl and phenyl, at least one R on each -OCHR-CHR- unit being hydrogen; where m is an integer selected from 1-100; where n is an integer selected from 8 and 9.

- A compound according to claim 1 wherein the double bonds exhibit opposite optical isomerism.
- 3. A compound according to claim 1 or claim 2, wherein m is an integer selected from 6-50.
- A compound according to any one of claim 1 to
   wherein most of the groups R are hydrogen.
- 5. A compound according to claim 4, wherein all of the groups R are hydrogen.
- 6. A process of preparation of a compound according to claim 1 comprising the reaction of alkylene oxide with linoleyl alcohol in the presence of a catalyst which is a Bronsted base.

- 7. A process according to claim 6, wherein the Bronsted base is one which will give an acceptable yield within the following parameters;
- (a) a reaction time of 48 hours maximum;
- (b) a temperature of 160°C maximum; and
- (c) a pressure of 1000 kPa maximum.
- 8. A process according to claim 6 or claim 7, wherein the Bronsted base is selected from alkali and alkaline earth metal hydroxides and alkoxides and metal hydrides.
- 9. A process according to claim 8, wherein the Bronsted base is selected from sodium methoxide, potassium hydroxide and sodium hydride.
- 10. A process according to any one of claims 1 to 6, wherein the linoleyl alcohol comprises part of a commercially-available fatty alcohol mixture having a linoleyl alcohol content of at least 15% by weight.
- 11. A process according to claim 10, wherein the linoleyl alcohol is at least 40% by weight.
- 12. A chemical composition which is essentially a blend of alkoxylated fatty alcohols, at least 15% (preferably at least 40%) by weight of which alcohols are compounds according to claim 1.

- 13. A process for preparing addition polymer particles, the process comprising polymerising in aqueous media unsaturated monomer in the presence of at least one compound of formula I according to any one of claims 1 to 5.
- 14. An aqueous dispersion of polymer particles stabilised by at least one compound according to any one of claims 1 to 4.
- 15. An aqueous dispersion according to claim 14, the dispersion being adapted for use as a coating composition.
- 16. Polymer particles of 100 nm maximum average diameter and comprising a core of a polymer of an ethylenically unsaturated monomer and a sheath comprising polyoxyalkylene chains wherein said polyoxyalkylene chains are derived from the covalent bonding of compounds of formula I according to any one of claims 1 to 5 with the core polymer.
- 17. A compound according to any one of claims 1 to 5 substantially as herein described with reference to any one of the Examples.
- 18. A process according to any one of claims 6 to 11 substantially as herein described with reference to any one of Examples 1 to 4.

- 19. A chemical composition according to claim 12 substantially as herein described with reference to any one of Examples 2 to 4.
- 20. An aqueous dispersion according to claim 14 substantially as herein described with reference to Example 5.

International Application No. PCT/AU 90/00565

	(o. PCT/AU 90/00565
I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, in	ndicate all) o 1
According to International Patent Classification (IPC) or to both National Classi	rication and irc
Int. Cl. 5 C07C 43/178, C08G 65/28	
II. FIELDS SEARCHED	<u> </u>
Minimum Documentation Searched 7	
Classification System   Classification Symbols	
IPC   C07C 43/178, C08G 65/28	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched	8
AU : IPC as above, Australian Classification 09.183.324.421	
III. DOCUMENTS CONSIDERED TO BE RELEVANT 9	<u>.</u>
Category*   Citation of Document, with indication, where appropriate,   of the relevant passages 12	Relevant to Claim No 13
A   AU,A, 32336/89 (HENKEL) 5 October 1989 (05.10.89), see page 16.	(6-11)
AU,B, 47222/89 (CIBA-GEIGY AG) 3 January 1991 (03.01.91), see pages 4,17 and 20.	(1-20)
A EP,A, 49358 (CONOCO INC) 14 April 1982 (14.04.82), especially pages 6 and 19.	(6 <b>-11</b> )
A,P WO,A, 90/05127 (HENKEL) 17 May 1990 (17.05.90), especially page 6.	(1-20)
* Special categories of cited documents: 10 "T" later document published international filing dat  "A" document defining the general state of the and not in conflict with and not in conflict with cited to understand the underlying the invention document but published on or after the international filing date  "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)  "O" document referring to an oral disclosure, involve an inventive step	e or priority date the application but   principle or theory   elevance; the be considered novel to involve an elevance; the be considered to p when the document
use, exhibition or other means  "P" document published prior to the international filing date but later than the priority date claimed  TV. CERTIFICATION  is combined with one or documents, such combinate a person skilled in the document member of the state of the	ion being obvious to a
Date of the Actual Completion of the   Date of Nailing of t	his International
International Search   Search Report   6 March 1991 (06.03.91)   12 March 199	
International Searching Authority   Signature of Authori  Australian Patent Office   Signature of Authori	zed Officer  R. EVANS

## ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL APPLICATION NO. PCT/AU 90/00565

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report		Patent Family Members					
AU	32336/89	BR JP US	8901521 1290643 4967017	DE NO	3811319 891368	EP NO	336263 891368
au	47222/89	CA JP	2006424 3024029	DK	6606/89	EP	403718
EP	49358	JP	57064629	NO	813305		•
WO	90/05127	DE	3837947	EP	370273		

END OF ANNEX

### THIS PAGE BLANK (USPTO)

# This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

#### **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

□ BLACK BORDERS
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
☐ FADED TEXT OR DRAWING
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
☐ LINES OR MARKS ON ORIGINAL DOCUMENT
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
Потить

#### IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

## THIS PAGE BLANK (USPTO)